

CREAM OFFSET SPECIFICATIONS

指标名称Items	单位Units				
定量Basis weight	g/m ²	68	78	98	118
定量横幅差CD difference of basis weight	g/m ²	≤3	≤3	≤3	≤3
厚度Thickness	μm	86-91	100-104	124-131	144-152
厚度横幅差CD difference of Thickness	%	≤5	≤5	≤5	≤5
松厚度Bulk	cm ³ /g	1.28-1.33	1.28-1.33	1.27-1.33	1.21-1.28
表面吸收重量 COBB	g/m ²	≤35	≤35	≤35	≤35
平滑度Bekk smoothness	S	28-40	28-40	21-40	18-36
CIE白度Whiteness	%	20-30	20-30	20-30	20-30
白度ISO Brightness	%	65-80	65-80	65-80	65-80
不透明度Opacity	%	≥93	≥95	≥97	≥97
表面强度Surface strength	m/s	≥2.2	≥2.2	≥2.2	≥2.2
水分Moisture	%	5.5-7.0	5.5-7.0	5.5-7.0	5.5-7.0
尘埃度Dust degree	pc/ m ²	≤60	≤60	≤60	≤60

备注：1、克重可以依据客户要求生产，指标依照相邻克重；2、本纸种最低克重为58克，最高克重120克。

REMARKS: 1, DIFFERENT GRAMMAGE GOODS CAN BE MANUFACTURED ACCORD TO CUSTOMER' S NEED, THE STANDARD IS SAME TO CONTIGUOUS ONE. 2, THE SUBSTANCE RANGE IS 58GSM-120GSM.