

VISCOM-DIGITAL - Wide Format Ink Jet Print Media

Issue date: 05/01/2005
Date last modification: 29/01/2013**03643 RI-JET 145 PVC REMOVABLE AR802 WK135 RIT/RED****Face Material**

Gloss white monomeric vinyl film.
Stamp on the back.

Type	Monomeric vinyl	
Colour and Finish	Gloss white	
Weight	109 g/m ² ±10%	ISO-536
Thickness	80 µ ±10%	ISO 534-80

Adhesive

Removable adhesive offering easy and clean removability from glass and from many other substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

Reference	AR802
Type	Acrylic removable
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+80°C
Shear	Alta
Tack	4 N/inch ²
Final Adhesion	3 N/inch

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m ² ±10%	ISO 536
Thickness	135 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

For advertising and promotional applications (window graphics and indoor posters, billboards and signs).

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

